



Release Notes for QXE1T1 6.2.23, Edition 1

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OWNED BY EPYGI TECHNOLOGIES, LTD. ANY COPYING, USE OR DISCLOSURE OF THE DOCUMENT OR THE INFORMATION CONTAINED HEREIN WITHOUT THE WRITTEN PERMISSION OF EPYGI TECHNOLOGIES, LTD. IS STRICTLY PROHIBITED.

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Epygi Technologies to be accurate as of the date of publication, is subject to change without notice. Epygi Technologies assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

Epygi, QX and Quadro are registered trademarks of Epygi Technologies, LLC. All other products and services are the registered trademarks of their respective holders.

1 Introduction

This Release Notes describes hardware and firmware requirements to use with the
QXE1T1 firmware 6.2.23 Date: August 23, 2018

Additional enhancements, bug fixes and known issues incorporated in this firmware will be listed as known.

Date: August 23, 2018

2 Requirements

2.1 Hardware Requirements

- This firmware (FW) can be used on QXE1T1 model only.
- The model name is written on the back plate of the unit and the model number is on the bottom label.

2.2 Firmware Requirements

Attention: The firmware upgrade to **6.2.23** can **ONLY** be done from 6.0.2 and higher versions.

2.3 Interaction with Other Epygi Software Releases

To achieve maximum compatibility with **QXE1T1 FW 6.2.23**, use the latest SW and FW versions:

- QX20, QX50, QX200, QX500, QX2000, QX3000, QXISDN4+ or ecQX configured in the **PSTN lines sharing (master-slave)** mode with QXE1T1 should be installed with 6.2.23 or higher FW version.
- QX-Quadro Configuration Console (QCC) SW 2.3 or higher should be used.
- Epygi Media Streamer (EMS) SW 2.4 or higher should be used.

3 New Features

The table below indicates a high-level list of new features that have been added beginning with the most recent QXE1T1 FW release.

Release	New Features
6.2.23	
6.2.22	Added support for the Twilio service as a new SMS Gateway . Use Twilio API for sending notifications via SMS.
	Added support for the Use Session Progress option instead of Ringin g for the external calls.
6.2.18	Added support for the new ecMon service. ecMon is a cloud-based monitoring service. It is a WEB application platform allowing centralized monitoring for ecQXs, QX IP PBXs and QX Gateways. It is a great tool for centralized monitoring and managing all active devices.
	Added support allowing to configure MTU size on LAN and VLAN interfaces.
	Added support to provide QX users with e-mail, sms and event notifications in case of calls (emergency calls, etc.) completed through the respective call routing rules.
	Added new failover reason – Other. The system will use next matching routing pattern(s) in case of Server Failure Responses (5xx messages) and Global Failure Responses (6xx messages).
	Added support for SNMP v3 .
	Added support for TLSv1.1 and TLSv1.2 .
	Added possibility to access QXE1T1 WEB GUI using HTTP. Enter the following line http://xxx.xxx.xxx.xxx/unsecure in the address bar of the browser to access WEB GUI, where xxx.xxx.xxx.xxx is the IP address or hostname of the QX.

Release	New Features
	<p>Security enhancements: Users will be redirected to HTTPS for the QX Login and Logout pages. This will allow to encrypt the traffic between user's device (PC, smartphone, etc.) and the QX.</p> <p>Note:</p> <ul style="list-style-type: none"> • Check and reconfigure Port Forwarding settings on the router, if the QX is located behind router to make sure that there is also Port Forwarding for HTTPS. • If you have already configured Port Forwardings to access the devices located on the QX LAN side, then check the entered address link to be HTTP (instead of HTTPS) or reconfigure the Port Forwarding to HTTPS.
	<p>Added a new Deactivate button on the IP Lines page allowing to change the status for selected group(s) of IP lines to inactive (free).</p>
6.2.1	<p>Added support to automatically archive Call History.</p> <p>Added the SSH FTP (SFTP) support, which allows to send the configuration backup files to an FTP server using the secure FTP connection.</p> <p>The Client Code Identification option can be activated and used by other billing systems as well as it is done for RADIUS server.</p> <p>Added support allowing to Restrict Simultaneous Calls for "SIP" call types.</p> <p>Added support for the SIP Registration Transport UDP/TCP/TLS options in the Extension's SIP Registration.</p> <p>Added Symmetric RTP option for IP Lines Settings. Select this option when the IP phone attached to the IP line is behind the NAT router.</p> <p>Uploading audio files for customizing any of the system or extension audio messages on the QXE1T1 has been simplified:</p> <ul style="list-style-type: none"> • Apart from the files in the (*.wav) format, the system can now accept (*.mp3) files for uploading as custom messages. • The (*.wav) and (*.mp3) files can now be uploaded directly to the system without the need to convert to the proper telephony format. The uploaded files will be automatically converted to the QX supported wav format: (CCITT u-law, 8 kHz, 16-bit, Mono). <p>General improvements and enhancements in the SIP TLS certificate.</p> <p>GUI enhancements on the Menu bar:</p> <ul style="list-style-type: none"> • Added device's current Date/Time. • Added device's hostname. <p>GUI enhancements for IP Lines page:</p> <ul style="list-style-type: none"> • Added support to allow quicker edits when moving between IP Lines. • Added support to allow quicker access to the attached extension's Admin and User settings. <p>GUI improvements and enhancements in the Extensions Management page.</p>
6.1.17	<p>Added support for Hosted PBX Survivability (HS) feature. The feature allows your company's telephones to work, even when the broadband link or Hosted PBX are down.</p> <p>Added IP Phones support with license key.</p> <p>Added the Keep Original Caller ID option for E1/T1 trunks in the call routing wizard.</p> <p>Added a new Search option in the QXE1T1 Online Help.</p>
6.1.10	
6.1.6	
6.1.5	<p>Added support for CCS DID service in E1/T1 Trunk Settings.</p>
6.0.13	

Release	New Features
6.0.10	
6.0.8	
6.0.2	

4 Changed Features

The table below provides a high-level list of changed features that have been changed beginning with the most recent QXE1T1 FW release.

Release	Changed Features
6.2.23	
6.2.22	Major Security Enhancements.
	GUI Enhancements for the following pages: <ul style="list-style-type: none"> • IP Lines • SMS Settings • Extensions Management • NAT Traversal • VoIP Carrier Wizard
6.2.18	Major Security Enhancements.
	Network and Broadcast IP addresses will not be included into Usable Host IP Range . These IPs will be reserved for network purposes.
	The Call Quality Warning in the System Events has been modernized to show information about the callee, caller and call date/time.
	The maximum length of API ID field for Clickatell SMS Gateway has been increased up to 128 symbols.
	GUI Enhancements for the following pages: <ul style="list-style-type: none"> • Admin Settings of the extensions (user and auto attendant) • User Settings of the extensions • Call History • IP Lines
	The default MTU size for VLAN interfaces has been decreased from 1500 to 1432 bytes.
6.2.1	The PSTN Gateways Line Sharing mechanism has been changed and updated, bringing more stability, improving the connection between PBXs and Gateways. Important Note: Please update the firmware version to 6.2.23 both on QXE1T1 and QX IP PBX to be able successfully connect the devices and share the lines.
	Hot Desking service enhanced regarding the voice notifications when login/logout on the public phones: <ul style="list-style-type: none"> • Added voice prompt asking user to login before using the phone. • Added voice prompt notifying user about login extensions in use. • Added voice prompt informing the user about the successful logging out.
	Added MC-Link , Flowroute , ClarityTel , Adiptel and Fusion as a new carrier to the VoIP Carrier Wizard list.
	Added support to download Extension's Call Detail Records for Successful, Missed and Unsuccessful Outgoing calls, when logged into the system using extension's credentials.
	Added support to exclude/include different CDR parameters in generated CDR reports for the Call History.
	Added support to display SRTP parameters in the Call History.
	Added MO=1 parameter in the SMS Settings .
	Added support for the following symbols "<", ">" in the password field for E-mail Settings .

Release	Changed Features
	<p>The backup configuration filename format has been updated and will include the installed firmware version of the QX: config_[Hostname]_[Firmware Version]_[Date/Time].bin</p> <p>The timezone database has been updated on QX Gateways:</p> <ul style="list-style-type: none"> The current local time has been corrected for Israel, Venezuela, Shri Lanka, Apia, Samoa and Fiji. Added new timezone Nukualofa, Tonga (GMT+14). <p>New Date/Time pickers have been implemented for all applicable GUI pages, allowing to select or define the date/time options easier and conveniently.</p> <p>Added support to allow/deny access to the Diagnostics and Reboot pages for QX localadmin.</p> <p>The Network Capture page has been moved to Maintenance→Diagnostics→Network Capture page.</p> <p>The Status→System Status→Memory page is redesigned and modernized.</p> <p>GUI Enhancements for E1/T1 trunk and DID Service pages.</p> <p>GUI Enhancements for Call Routing Table.</p> <p>GUI Enhancements on the Setup→Licensed Features page.</p> <p>The 5061 will be used as default TLS port for SIP.</p>
6.1.17	<p>The maximum Number of Call Records to Download is increased to 10000 in the Status→Call History→Automatic Backup.</p> <p>The maximum length of Connection Name field for PPTP and L2TP has been increased up to 64 symbols. Support for the following symbols "@", "-", ".", "_" is added.</p> <p>Added support allowing to enable/disable entries in the Authorized Phones.</p> <p>The Blueface Ireland, Blueface Italy and Blueface UK carriers have been removed from the VoIP Carrier Wizard list.</p> <p>Added SoTel/VoIPLINK as a new carrier to the VoIP Carrier Wizard list.</p>
6.1.10	<p>Added support in Extensions Multiple Editing for the following fields: Password and Confirm password from General Settings page and Authentication User Name from SIP Advanced settings.</p> <p>The behavior for the VoIP Carrier Wizard is changed. The new Authentication by IP Address checkbox allows bypassing the Account Name and Password information and filling the SIP Server and SIP Server Port information only for the carriers not requiring account authentication.</p> <p>Added Blueface Ireland, Blueface Italy, Blueface UK, BINARY NETWORKS, IP Directions, MyNetFone and ThinkTel Communications as new carriers to the VoIP Carrier Wizard list.</p> <p>Kebu.it carrier has been removed from the VoIP Carrier Wizard list.</p> <p>The old password will not be required when change the Phone Access Password for Administrator.</p> <p>The LAN IP Address of the backup configuration displayed in the shell window, while restoring previously backed up configuration file.</p> <p>Loadlogo.cgi hidden page (for updating company details) has been renamed (changed) to uploadlogo.cgi</p>
6.1.6	
6.1.5	
6.0.13	
6.0.10	
6.0.8	
6.0.2	

5 Fixed Issues

Issues fixed since version 6.2.22:

T: Title
D: Description

20328	T:	Using some special symbols in the admin GUI changed password may cause problem with accessing GUI management.
	D:	
20325	T:	The QX Security Diagnostics show nothing in the security reports regarding the admin's GUI and phone passwords weakness.
	D:	

6 Known Issues

T: Title
D: Description
C: Consequences
Fix: How to avoid the situation, or what to do in case the situation has occurred

17404	T:	Call which is done after Call Relay (*2) on auto attendant is not shown in the Call History
	D:	Only the call to attendant is shown in the call history. The call leg after call relay is missing in the call history in case if the external caller is terminating the call first.
	C:	
	Fix:	Workaround: Use feature code *1 instead of *2 for call relay. Will be fixed in future release.

7 General Hints

7.1 Technical Advisory

Some system information (Call History and Pending Events) may be lost when QXE1T1 is powered down. You may maximum lose the portion of the above-mentioned system information, which occurred during last hour before the QX is powered down. It's recommended to enable **Call History – Archiving** to minimize the loss of Call History.

7.2 Firmware Update

It is recommended to execute the update by downloading the firmware first to a PC located in the LAN side of the QXE1T1 and perform the firmware update from the LAN side. This is to ensure that the Internet connection will not affect the upgrade process.

Attention: It is recommended to back up the configuration for **emergency purposes** prior to upgrading the firmware. You can do that from **Maintenance→Backup/Restore→Backup and download current Configuration** page. The current configuration will remain after the firmware update. Moreover, all custom messages and call history will be saved during the upgrade.

To perform the manual firmware update:

1. Go to the **Maintenance→Firmware→Manual Firmware Update** page.
2. Click the **Download Configuration** link to back up the current configuration, if needed.
3. Click **Choose File** button to browse for **image.bin** file.
4. Click **Save** to start uploading the file.
5. Click **Yes** to proceed the firmware upgrade.

Note: The update process takes about **5** minutes. Normal operation will be stopped during that time.

7.3 Limitations and Restrictions

- The **Network Capture** size is limited to **24 MB**. This will put a limitation on the duration of captured file.
- The **Call Capture** duration is limited to **160** seconds.
- The **DSP Capture** duration is limited to **160** seconds.